



**Pin-Belegung /
Pin Assignment**

CN1	CN2
01	04
02	01
03	05
04	03

USB-Adapter

- zur Benutzung mit Kombo Tastatur

Anschlüsse:	USB-2.0-Stecker (Typ A) , Mini-DIN 6-Buchse (PS/2)
Einschaltwiderstand:	max. 5 Ω
Isolationswiderstand:	min. 10 MΩ
Material Gehäuse:	PVC 45P, PE
Material USB:	Eisen, vergoldete Pins
Material PS/2:	vernickeltes Eisen, vergoldete Pins
Innenleiter AD:	0,7 mm

USB adapter

- to be used with combo keyboard

Connectors:	USB 2.0 male (type A), Mini-DIN 6 female (PS/2)
ON resistance:	max. 5 Ω
Insulation resistance:	min. 10 MΩ
Material housing:	PVC 45P, PE
Material USB:	iron, gold-plated pins
Material PS/2:	nickel-plated iron, gold-plated pins
Inner conductor OD:	0.7 mm

Änderungen

Datum	Name	gez.:	Datum	Name	Bezeichnung	Blatt
		gez.:	03.03.2022	aw	USB ADAP A-M/PS2-F	1/1
		gepr.:	03.03.2022	aw		
		Norm:			Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change					68918	

